

Riego

SPECIFICATION

Specifications

- Heavy brass construction for durability and reliability
- Pressure balancing diverter valve with ceramic cartridge ensures anti-scald operation for life long trouble free service
- Single lever handle operation allows both volume and temperature control
- Max temperature limit stop for added safety
- Integral stop valves for easy maintenance
- Dual inlet and outlet ports – 1/2" CxC soldering & 1/2" NPT thread
- Adjustable installation depth from 1-3/8" (35mm) to 2-9/16" (65mm)
- Locking mechanism to ensures diverter functionality at low operating pressure below 20 psig
- Integral bubble level provided on rough-in valve to ensure easy and straight installation
- Mud guards are provided to protect trim finish
- Brass trim cover plate with design handle
- 8" ABS self-cleaning square rain shower head with 8" long shower arm
- Design tub spout with an easy installation quick connector
- Matching with W series and L series

Flow Rate

- 4.5 gpm @ 60 psig for tub spout
- 2.0 gpm @ 60 psig for shower head

Finish

- CP (Polished Chrome)

Codes and Standards

- ANSI/ASME A112.18.1
- CSA B125.1
- IAPMO / cUPC Listed
- EPA Watersense Listed

Warranty

- Limited Lifetime Faucet Warranty against material and manufacturing defects for residential use.
- 2 Year Limited Warranty on all industrial, commercial and business applications.

M Series Tub and Shower Set Model # L9420

